




COLOR FLEX™

SPEC SHEET FOR ROLLED FLOORING

SHORE HARDNESS	ASTM D-2240	60 +/- 5
DENSITY	ASTM D-792	75 lbs. cu. ft.
ELONGATION	ASTM D-412	70%
REBOUND	ASTM D-3574 (5/16")	45-60 %
TENSILE	ASTM D-412	200 psi
TABER ABRASION	ASTM C-501	.45
FLAME SPREAD	ASTM E-84	125
SMOKE DEVELOPED	ASTM E-84	Passes 250
COMPRESSION SET	ASTM D-395B	12 % or less
OZONE EXPOSURE	ASTM D-1149-86	No adversities
AGING RESISTANCE	ASTM D-750	No change
TEAR STRENGTH	ASTM D-624	50 psi
Granulate:	1-3 mm EPDM	
Binder:	Urethane	
Warranty:	3 Years by Manufacturer Materials only.	



Skive / Knife marks on product is an inherent characteristic of using re-cycled rubber and will not be viewed as an appropriate reason for rejecting the final finished product.

Kiefer U.S.A. and its contractors shall not be liable for incidental or consequential losses, damages, or expenses, directly or indirectly arising from the sale, handling or use of the goods, or from any other cause relating thereto, and their liability hereunder in any case is expressly limited to the replacement of goods of complying with this agreement, or, at their election, to the repayment of, or crediting Buyer with, an amount equal to the purchase price of such goods, whether such claims are for breach of warranty negligence.

Adhesive:	Chemrex CX-941 one-component polyurethane adhesive
Line Paint:	Suitable for interior or exterior synthetic rubber.
Storage:	Rolls on side, minimum 55 degrees Fahrenheit, less than 50% humidity.
Sub-Flooring:	Should not vary more than 1/8" in ten ft.
New Concrete/Asphalt:	30 days cure prior to installation of rubber.
Maintenance:	Under normal usage light mopping; common detergents if needed.
STANDARD ROLL:	4ft WIDE BY PREDETERMINED
SHIPMENT:	F.O.B. Factory

Physical properties can vary by product type; above information applies.

Every effort is made in the manufacture of the prefabricated matting for size, color and density consistency within a given lot #, slight variations can occur from lot # to lot #.



2910 Falling Waters Blvd
Lindenhurst, IL 60046
800.322.5448