

Characteristics	Standards	Units	Requirements	Values From Manufacturing Controls*
Elongation at Break	ASTM D412	%	≥100	≥202
Tensile Strength	ASTM D412	psi	≥75	≥131
Durometer Hardness (Wear Layer)	ASTM D2240	Shore A	55 ±5	50
Durometer Hardness (Backing)	ASTM D2240	Shore A	40 ±5	35
Abrasion Resistance (H18 wheels, 1000g, 1000 cycles)	ASTM D3389	g loss	≤2.0	≤1.55
Critical Radiant Flux	ASTM E648	W/cm ²	≥0.1	≥0.15
Chemical Resistance	ASTM F925	-	≤ Slight Change	Compliant**
Resistance to Heat	ASTM F1514	ΔE	≤8.0	Compliant
Resistance to Light	ASTM F1515	ΔE	≤8.0	Compliant
Slip/Skid Resistance (Dry)	EN 13036-4	-	≥80	Compliant
Slip/Skid Resistance (Wet)	EN 13036-4 (WA)	-	≥47	Compliant
Shock Absorption	EN 14808 (WA)	%	35-50	Compliant
Vertical Deformation	EN 14809 (WA)	mm	0.6-2.5	Compliant
Spike Resistance	EN 14810	ΔTr%	≤20	Compliant
Spike Resistance	EN 14810	ΔEb%	≤20	Compliant

Health and Environmental Attributes

Indoor Air Quality (VOC Emissions)	French Decree № 2011-321 GREENGUARD Certification GREENGUARD Gold	
Health-Conscious Product	Mondotrack EI is manufactured in a facility that has ISO 9001, ISO 14064 and ISO 50001 certifications. At Mondo, we pride ourselves on producing premium high-quality rubber flooring products that can be utilized in areas with stringent health and safety controls; we do not use red listed ingredients (2024 LBC Red List CASRN Guide) to manufacture our rubber flooring products, which includes but is not limited to harmful chemicals of concern like bisphenol A (BPA), formaldehyde, halogens, heavy metals, isocyanates, phthalates, polyvinyl chloride (PVC), perfluorinated compounds (PFC) and perfluoroalkyl and polyfluoroalkyl substances (PFA). Also, a product-specific Type III Environmental Product Declaration (EPD) is available for this product. Mondotrack EI complies with CDPH v1.2-2017 (California Section 01350) and is GREENGUARD Gold certified.	
Materials and Resources (% by Weight)	Post-Consumer Recycled Content	≥23%
	Pre-Consumer Recycled Content	≥18%
	Rapidly Renewable Materials	≥9%

Weight and Dimensions	Metric	Imperial
Thickness (ASTM F387)	14.0 mm (±0.3 mm)	0.531" (±0.011")
Weight	≥13.0 kg/m ²	≥2.66 lb/ft ²
Roll Width	0.92 m to 1.83 m	3' to 6'
Roll Length	15 m [min. 6 m; max. 15 m]	49.2' [min. 19.68'; max. 49'2"]

*Values obtained from manufacturing controls can vary between production lots and do not constitute representations or warranties as to any particular production lot. Mondo reserves the right to modify product design and/or specifications at any time without notice.

**For the complete list of chemicals tested, concentrations and contact time, please communicate with Mondo's Technical Department.

WARNING ON REQUIREMENTS: MINIMAL REQUIREMENTS TO BE RESPECTED AT ALL TIMES.

WARNING ON VALUES: ANY MANUFACTURING VALUE POSTED REGARDING FIRE SAFETY AND ANY INDOOR AIR QUALITY CERTIFICATE AWARDED ONLY APPLIES TO INDOOR INSTALLATIONS OVER CONCRETE AND MONDO PRODUCTS DESIGNED FOR THIS PURPOSE.

Warranty

Mondo Limited Material 10-year Warranty. Please refer to current copy of the warranty for terms and conditions. Additional information and warranty copy may be obtained at www.mondoworldwide.com or through our Technical Department at sports.technical@mondousa.com. USA 800.361.3747 · CANADA 800.663.8138